

1. Genset 450 kVA - 50Hz



POWERED BY



2. Technical informations

Generator Specifications	Unit	Description		
Regulation class		ISO8528		
Frequency	Hz	50		
Power Factor		0.8		
Three Phase Voltage	Vca	380 - 220 / 400 - 231		
Operating System		Stand-By	Prime	COP
Genset Power	kVA / kW	450 / 360	413 / 331	280 / 224
Diesel Engine Power	CV	547.2	495.6	335,4
Fuel Tank		600 liters on the base		
Consumption $\pm 5\%$	l/h	89.2	79.5	53,5
Fuel Tank Autonomy	h	4.4	5	11,15
Battery		2 x 12V - 150Ah - 900CCA		

Engine Specifications	Unit	Description	
Model		DC13 072A 02-12	
Brand		SCANIA	
Application		Stationary	
Rotation	rpm	1500	
Configuration		04- stroke / 6 Cylinders in line	
Bore x Stroke	mm	130 x 160	
Aspiration Type / Injection System		Turbo Aftercooler / Eletronic Direct	
Displacement	l	12.7	
Compression Ratio		16.3:1	
Alternator, standart equipment	A	100	
Starter, standart equipment	Vcc - kW	24 - 06	
Cooling System		Water + Air + Blowing Ventilation System	
Coolant Total Capacity	l	50	
Coolant Specification		Havoline Xtended Life Premix 50/50	
Lube Oil Specification		SAE 15W40 / ACEA E3, E4, E5 or E7	
Lube Oil liter Capacity with filter	l	36	
Lube Oil Filter Replacement Interval	h	500	
Fuel Type Specification		S10	
Fuel Filter		Pre-Filter	Main
Fuel Filter Specification		Paper Filter element 10 micron	Paper Filter element 6 micron
Oil Change Intervals	h	500	
Preheating resistance		2000W - Standart to automatic Genset	

Alternator Specification	Description
Type	Brushless
Excitation	With Auxiliary Coil
Voltage Regulator	Electronic incorporated with dynamic response from 8 up to 500ms ; static control of 0,5%
IP Rating	IP23
Isulation Class	180°C (Class H)
Harmonic Distortion Without Load	< 5%
Short Circuit Current	3x IN during 10 s
Leads	12
Connection Box	Connectable in 3 Tensions
Bearing	Single
Cooling	Air
Mounting types	BT15
Winding Pitch	Shortened 2/3
Impregnation	Industrial Salinity Resistant with Salt Concentration =< 1 g/m3

Command Panel Specifications	Unit	Description
Type		Manual Automatic
Single Without Ramp		DEEP SEA DS4520
Single With Ramp		DEEP SEA DS8620
Parallel Without Ramp		DEEP SEA DS8610 + DS331
Parallel With Ramp		DEEP SEA DS8610 + DS8660
Three Phase Voltage	Vca	380 - 220 / 400 - 231
IP Rating		IP-23
Dimensions (H x W x D)	mm	1200 x 600 x 255
Protection		Manual thermomagnetic circuit-breaker - tripolar fixed
Parallelism Connection between Generators		Motorized Circuit Breaker
Battery Charger		YES NO

Assembly Specifications	Unit	Description
Type		Open Skid Canopy
Exhaust System		Industrial 6" and stainless-steel bellows; Hospitalar 6" and stainless-steel bellows
Width (W)	mm	1180 1180
Length (L)	mm	3693 4640
Height (H)	mm	1970 2285
Empty Weight	kg	3044 3650
Impregnation		Polyester powder electrostatic (base in black color and Canopy in blue color)
Impregnation type		Textured
Salt Spray Resistance Assembly Specifications		Minimum 500h (on phosphatized plate)
Paint Thickness		80 µm [microtexturized]
Levels of noise	1,5 m	dB(A) 117 85
	7,0 m	dB(A) 101 NA

NA - Not Available

Updated: 07/07/2022

