

1. Genset 330 kVA - 50Hz**POWERED BY****2. Technical informations**

Generator Specifications	Unit	Description		
Regulation class		ISO8528		
Frequency	Hz	50		
Power Factor		0.8		
Three Phase Voltage	Vca	380 - 220 / 400 - 231		
Operating System		Stand-By	Prime	COP
Genset Power	kVA / kW	330 / 264	300 / 240	157 / 125
Diesel Engine Power	CV	400	362.5	82.8
Fuel Tank		600 liters on the base		
Consumption ± 5%	l/h	68.9	61.6	37.9
Fuel Tank Autonomy	h	8.7	9.7	15.8
Battery		2 x 12V - 150Ah - 900CCA		

Engine Specifications	Unit	Description	
Model		DC09 072A 02-13	
Brand		SCANIA	
Application		Stationary	
Rotation	rpm	1500	
Configuration		04- stroke / 5 Cylinders in line	
Bore x Stroke	mm	130 x 140	
Aspiration Type / Injection System		Turbo Aftercooler / Eletronic Direct	
Displacement	l	9.3000000000000001	
Compression Ratio		16:1	
Alternator, standart equipment	A	100	
Starter, standart equipment	Vcc - kW	24 - 06	
Cooling System		Water + Air + Blowing Ventilation System	
Coolant Total Capacity	l	38	
Coolant Specification		Scania Coolant Ready Mix 50/50	
Lube Oil Specification		SAE 15W40 / ACEA E3, E4, E5 or E7	
Lube Oil liter Capacity with filter	l	36	
Lube Oil Filter Replacement Interval	h	500	
Fuel Type Specification		S10	
Fuel Filter		Pre-Filter	Main
Fuel Filter Specification		Paper Filter element 10 micron	Paper Filter element 6 micron
Oil Change Intervals	h	500	
Preheating resistance		2000W - Standart to automatic Genset	

DIESEL GENSET**Genset SGD330.50**

Alternator Specification		Description	
Type		Brushless	
Excitation		With Auxiliary Coil	
Voltage Regulator		Electronic incorporated with dynamic response from 8 up to 500ms ; static control of 0,5%	
IP Rating		IP23	
Insulation Class		180°C (Class H)	
Harmonic Distortion Without Load		< 5%	
Short Circuit Current		3x IN during 10 s	
Leads		12	
Connection Box		Connectable in 3 Tensions	
Bearing		Single	
Cooling		Air	
Mounting types		B15T	
Winding Pitch		Shortened 2/3	
Impregnation		Industrial Salinity Resistant with Salt Concentration =< 1 g/m3	

Command Panel Specifications		Unit	Description	
Type			Manual	Automatic
Single Without Ramp			DEEP SEA	
			DS4520	
Single With Ramp			DEEP SEA	
			DS8620	
Parallel Without Ramp			DEEP SEA	
			DS8610 + DS331	
Parallel With Ramp			DEEP SEA	
			DS8610 + DS8660	
Three Phase Voltage	Vca		380 - 220 / 400 - 231	
IP Rating			IP-23	
Dimensions (H x W x D)	mm		1200 x 600 x 255	
Protection			Manual thermomagnetic circuit-breaker - tripolar fixed	
Parallelism Connection between Generators			Motorized Circuit Breaker	
Battery Charger			YES	NO

Assembly Specifications		Unit	Description	
Type			Open Skid	Canopy
Exhaust System			Industrial 6" and stainless-steel bellows	Hospitalar 6" and stainless-steel bellows
Width (W)	mm		1180	1180
Length (L)	mm		3425	4250
Height (H)	mm		1853	2085
Empty Weight	kg		2567	3087
Impregnation			Polyester powder electrostatic (base in black color and Canopy in blue color)	
Impregnation type			Textured	
Salt Spray Resistance Assembly Specifications			Minimum 500h (on phosphatized plate)	
Paint Thickness			80 µm [microtexturized]	
Levels of noise	1,5 m	dB(A)	117	85
	7,0 m	dB(A)	101	NA

NA - Not Available

Updated: 04/04/2022

